# Air Conditioning

## **Product Information**

PCA-RP140KAQ (Single Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

### **Key Features**

- Stylish indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections
- Automatic air speed adjustment
- High/low ceiling height modes



Air Conditioning | Heating Ventilation | Controls



## **Product Information**

PCA-RP140KAQ (Single Phase) **Standard Inverter Heat Pump** Ceiling Suspended System

Making a World of Difference

# Air Conditioning

| PCA-RP - INDOOR UNITS                       |                        | PCA-RP140KAQ               |
|---|------------------------|----------------------------|
| CAPACITY (kW)                               | Heating (nominal)      | 16.0 (5.0-18.0)            |
|   | Cooling (nominal)      | 13.6 (5.5-15.0)            |
|   | Heating (UK)           | 13.6 (4.25-15.3)           |
|   | Cooling (UK)           | 12.5 (5.05-13.8)           |
| SHF (nominal & UK)                          |                        | 0.72                       |
| COP / EER (nominal)                         |                        | 3.41 / 2.81                |
| SCOP / SEER (BS EN14825)                    |                        | 3.5 / 3.2                  |
| ErP ENERGY EFFICIENCY CLASS Heating/Cooling |                        | N/A                        |
| AIRFLOW (I/s)                               | Lo-Mi1-Mi2-Hi          | 400-433-483-533            |
| PIPE SIZE mm (in)                           | Gas/Liquid             | 15.88 (5/8") / 9.52 (3/8") |
| SOUND PRESSURE LEVEL (dBA)                  | Lo-Mi1-Mi2-Hi          | 41-43-45-48                |
| SOUND POWER LEVEL (dBA)                     |                        | 68                         |
| DIMENSIONS (mm)                             | Width x Depth x Height | 1600 x 680 x 230           |
| WEIGHT (kg)                                 |                        | 39                         |
| ELECTRICAL SUPPLY                           |                        | Fed by Outdoor Unit        |
| FUSE RATING (BS88) - HRC (A)                |                        | 6                          |
| INTERCONNECTING CABLE No. Cores             |                        | 4                          |


| PUHZ-P - OUTDOOR UNITS                           |                           | PUHZ-P140VHA3         |
|--|---------------------------|-----------------------|
| SOUND PRESSURE LEVEL (dBA) Heating/Cooling       |                           | 56 / 52               |
| SOUND POWER LEVEL (dBA) Cooling                  |                           | 73                    |
| WEIGHT (kg)                                      |                           | 99                    |
| DIMENSIONS (mm)                                  | Width x Depth x Height    | 950 x 330 + 30 x 1350 |
| ELECTRICAL SUPPLY                                |                           | 220-240v, 50Hz        |
| PHASE  |                           | Single                |
| SYSTEM POWER                                     | Heating/Cooling (nominal) | 4.69 / 4.84           |
| INPUT (kW)                                       | Heating/Cooling (UK)      | 4.17 / 4.11           |
| STARTING CURRENT (A)                             |                           | 15.0                  |
| SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX] |                           | 22.21 / 23.38 [30.4]  |
| FUSE RATING (BS88) - HRC (A)                     |                           | 40                    |
| MAINS CABLE No. Cores                            |                           | 3                     |
| MAX PIPE LENGTH (m)                              |                           | 50                    |
| MAX HEIGHT DIFFERENCE (m)                        |                           | 30                    |
| CHARGE R410A (kg)                                |                           | 4.5                   |

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length. Duty/standby not available on SUZ-KA50/60/71VA4. High efficiency filter optional.




### **DIMENSIONS**


#### Front View



#### **Upper View**



### **Back View**





Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


forigin: United Kingdom - Japan - Thailand - Malaysia. ("Mitsubish) Electric Europe 2015. Mitsubish) Electric are trademarks of Mitsubish Electric Europe B.V. The company reserves the alea any variation in technical specification to the outprend described, or to withdraw or replace products without prior notification or public announcement. Mitsubish Electric is constantly developing withing its products. All descriptions, flustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to any's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment







