# Air Conditioning

## **Product Information**

PCA-RP140KAQ (Three Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference

## mr.slim.



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

### **Key Features**

- Stylish indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections
- Automatic air speed adjustment
- High/low ceiling height modes



Air Conditioning | Heating Ventilation | Controls



# **Product Information**

PCA-RP140KAQ (Three Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference

PCA-RP - INDOOR UNITS		PCA-RP140KAQ
CAPACITY (kW)	Heating (nominal)	16.0 (5.0-18.0)
	Cooling (nominal)	13.6 (5.5-15.0)
	Heating (UK)	13.6 (4.25-15.3)
	Cooling (UK)	12.5 (5.05-13.8)
SHF (nominal & UK)		0.72
COP / EER (nominal)		3.41 / 2.81
SCOP / SEER (BS EN14825)		3.5 / 3.2
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	N/A
AIRFLOW (I/s)	Lo-Mi1-Mi2-Hi	400-433-483-533
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	41-43-45-48
SOUND POWER LEVEL (dBA)		68
DIMENSIONS (mm)	Width x Depth x Height	1600 x 680 x 230
WEIGHT (kg)		39
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

Air Conditioning

PUHZ-P - OUTDOOR UNITS		PUHZ-P140YHA Three Phase	3
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		56 / 52	
SOUND POWER LEVEL (dBA) Cooling		73	
WEIGHT (kg)		101	
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 1350	
ELECTRICAL SUPPLY		380-415v, 50Hz	
PHASE		Three	
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	4.69 / 4.84	
	Heating/Cooling (UK)	4.17 / 4.11	
STARTING CURRENT (A)		5.0	
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		8.48 / 8.82 [13.9]	
FUSE RATING (BS88) - HRC (A)		16	
MAINS CABLE No. Cores		5	
MAX PIPE LENGTH (m)		50	
MAX HEIGHT DIFFERENCE (m)		30	
CHARGE R410A (kg)		4.5	


#### 3 Three Phase

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length. High efficiency filter optional.




#### DIMENSIONS


#### Front View



#### **Upper View**



#### Back View



MITSUBISHI ELECTRIC Changes for the Better

#### Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysia. @Mitsubishi Electric Europe 2015. Mitsubishi Bectric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prive notification or public amouncement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sala, a copy of which is available on request. Third-parky product and brand manes may be trademarks or registred trademarks of their respective owners.



www.greengateway.mitsubishielectric.co.uk Mitsubishi Electric UK's commitment to the environment



mitsubishielectric2



Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electriciar/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Misubikit Becritics air conditioning and heat pump systems contain fluorinated greenhouse gases R410A, R407C and R134a.

Effective as of April 2015