

# Ecodan<sup>®</sup> Air Source Heat Pumps for domestic space heating and hot water

With Flow Temperature Controller 2



The Mitsubishi Electric Ecodan is designed to meet the demands of today's domestic hot water and heating requirements.

Simple to install, cost effective for the end-user and with outstanding energy efficiency it is ideal for designers, installers and users. Inverter-driven heat pump technology offers a low carbon alternative to traditional boilers in modern buildings, whether they are new build or refurbishments.

- 30 - 50% reduction in CO<sub>2</sub> emissions
- Low running costs
- Easy to install - self contained unit only requiring water and electric connections
- No gas supply, flues or ventilation required
- No need for groundwork or external pumps
- Single phase power supply with a low starting current
- Three phase option available (14kW)
- Even higher running cost savings and CO<sub>2</sub> reductions with under floor heating systems
- Low maintenance
- Reduced VAT from 17.5% to 5% for domestic applications
- Comparable installation costs to a modern gas-fired condensing boiler
- Low noise

Technical Information >



# Ecodan® Air Source Heat Pumps

## for domestic space heating and hot water

**ecodan®**  
Advanced Heating Technology

With Flow Temperature Controller 2

Specifications


Specifications		PUHZ-W50VHA	PUHZ-W85VHA2	PUHZ-HW140VHA2	PUHZ-HW140YHA2
Dimensions (mm)	Width	950	950	1020	1020
	Depth	330+30*	330+30*	330+30*	330+30*
	Height	740	943	1350	1350
Weight (kg)		64	77	134	148
Airflow (m <sup>3</sup> /min)		50	55	100	100
Nominal sound level (dBA)		45 <sup>^</sup>	48 <sup>^</sup>	53 <sup>^</sup>	53 <sup>^</sup>
Low noise mode (dBA) @ 7°C		40	42	46	46
Guaranteed operating range (Outdoor)		-15~+35°C	-20~+35°C	-25~+35°C	-25~+35°C
Electrical Supply		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	380-415v, 50Hz
Phase		Single	Single	Single	3
Running current (A) [Max]		5.4 [13]	10.3 [23]	14.9 [35]	5.1 [13]
Fuse Rating (MCB sizes BS EN 60898) (A)		16	25	40	16
Heating A2/W35	Capacity (kW)	5.0 (1.5-5.0)	8.5 (2.6-8.5)	14.0 (4.2-14.0)	14.0 (4.2-14.0)
	COP	3.13	3.17	3.11	3.11
	Power Input (kW)	1.60	2.68	4.52	4.52
	Nominal flow rate (L/min)	14.3	25.8	40.1	40.1
Heating A7/W35	Capacity (kW)	5.0 (1.5-5.0)	9.0 (2.7-9.0)	14.0 (4.2-14.0)	14.0 (4.2-14.0)
	COP	4.10	4.18	4.25	4.25
	Power Input (kW)	1.22	2.15	3.31	3.31
	Nominal flow rate (L/min)	14.3	25.8	40.1	40.1
*Grille <sup>^</sup> At distance of 1m from outdoor unit					
Nominal operating condition		Nominal operating condition			
Heating (A2/W35)	Outside air temperature (dry) +2°C Outside air temperature (humid) +1°C Water temperature (inlet/outlet) +30/+35°C	Heating (A7/W35)	Outside air temperature (dry) +7°C Outside air temperature (humid) +6°C Water temperature (inlet/outlet) +30/+35°C		

## Flow Temperature Controller 2

To allow the home owner to continue to operate both their central heating and hot water time clocking using a commonly available two-channel controller, we have introduced the Flow Temperature Controller (FTC2) interface.

In a Space Heating mode the FTC2 will ensure that Ecodan operates at optimum efficiency, varying the flow temperature to either the radiator or under floor heating system to meet a homes heating requirements.

In a Water Heating mode the FTC2 will allow the Ecodan to work with leading brands of water storage tanks. It is, however, important to consider that the overall performance of the system in Water Heating mode will be very dependant on the thermal performance of the storage tank's heat exchanger. With the packaged systems we offer, the heat exchangers have been designed to offer an optimised performance across the whole Ecodan water flow temperature range and these performances have been tested and verified. We therefore strongly recommend that similar consideration is given to the specification of any hot water storage tank before being considered for operation with the Ecodan.



Telephone: **01707 278666**

Fax: **01707 278592**

email: [heating@meuk.mee.com](mailto:heating@meuk.mee.com)

web: [www.mitsubishielectric.co.uk/heating](http://www.mitsubishielectric.co.uk/heating)

UNITED KINGDOM Mitsubishi Electric Europe Heating Systems  
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England.  
General enquires Telephone: 01707 282880 Fax: 01707 278674

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland.  
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thailand – Malaysia. ©Mitsubishi Electric Europe 2010. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Printed in February 2010

SAP No. 217700



Certificate Number: MCS HP0002  
Product Reference: PUHZ-W50VHA-(BS)  
PUHZ-W85VHA2-(BS), PUHZ-HW140VHA2/YHA2-(BS)



Licence Number:  
UK/31/001 - PUHZ-W50VHA-(BS)  
UK/31/002 - PUHZ-W85VHA2-(BS)  
UK/31/003 - PUHZ-HW140VHA2/YHA2-(BS)

Printed on paper that contains fibre from forests certified according to the principles of the Forest Stewardship Council. The Forest Stewardship Council (FSC) is an international network promoting responsible management of the world's forests.