# Air Conditioning

### **Product Information**

PCA-RP100KAQ (Single Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

### **Key Features**

- Stylish indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections
- Automatic air speed adjustment
- High/low ceiling height modes



Air Conditioning | Heating Ventilation | Controls



### **Product Information**

PCA-RP100KAQ (Single Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference

## Air Conditioning

PCA-RP - INDOOR UNITS		PCA-RP100KAQ
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-12.5)
	Cooling (nominal)	9.4 (4.9-11.2)
	Heating (UK)	9.5 (3.85-10.65)
	Cooling (UK)	8.65 (4.5-10.3)
SHF (nominal & UK)		0.77
COP / EER (nominal)		3.41 / 3.00
SCOP / SEER (BS EN14825)		3.8 / 5.1
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A/A
AIRFLOW (I/s)	Lo-Mi1-Mi2-Hi	367-400-433-467
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	37-39-41-43
SOUND POWER LEVEL (dBA)		63
DIMENSIONS (mm)	Width x Depth x Height	1600 x 680 x 230
WEIGHT (kg)		36
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4


PUHZ-P - OUTDOOR UNITS		PUHZ-P100VHA4
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		54 / 50
SOUND POWER LEVEL (dBA) Cooling		70
WEIGHT (kg)		75
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER	Heating/Cooling (nominal)	3.28 / 3.13
INPUT (kW)	Heating/Cooling (UK)	2.92 / 2.66
STARTING CURRENT (A)		12.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		15.35 / 14.63 [28.7]
FUSE RATING (BS88) - HRC (A)		32
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		50
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg)		3.0

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length. Duty/standby not available on SUZ-KA50/60/71VA4. High efficiency filter optional.




### **DIMENSIONS**


#### Front View



### **Upper View**



#### **Back View**





Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881
IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Country of origin: United Kingdom - Japan - Thailand - Malaysia. (Mitsubishi Electric Europe 2015. Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Missubishi Electric is constantly developing and improving its products. All descriptions, llustrations, drawings and specifications in this publication present only general particulars and shall not from part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.










Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)





Mitsubishi Electric UK's commitment to the environment



