Air Conditioning

Product Information

PCA-RP100KAQ (Three Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

Key Features

- Stylish indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections
- Automatic air speed adjustment
- High/low ceiling height modes



Air Conditioning | Heating Ventilation | Controls



Product Information

PCA-RP100KAQ (Three Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference

Air Conditioning

PCA-RP - INDOOR UNITS		PCA-RP100KAQ
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-12.5)
	Cooling (nominal)	9.4 (4.9-11.2)
	Heating (UK)	9.5 (3.85-10.65)
	Cooling (UK)	8.65 (4.5-10.3)
SHF (nominal & UK)		0.77
COP / EER (nominal)		3.41 / 3.00
SCOP / SEER (BS EN14825)	3.8 / 5.1
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A/A
AIRFLOW (I/s)	Lo-Mi1-Mi2-Hi	367-400-433-467
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	37-39-41-43
SOUND POWER LEVEL (dBA)		63
DIMENSIONS (mm)	Width x Depth x Height	1600 x 680 x 230
WEIGHT (kg)		36
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

PUHZ-P - OUTDOOR UNITS		PUHZ-P100YHA2 3 Three Phase
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		54 / 50
SOUND POWER LEVEL (dBA) Cooling		70
WEIGHT (kg)		77
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943
ELECTRICAL SUPPLY		380-415v, 50Hz
PHASE		Three
SYSTEM POWER	Heating/Cooling (nominal)	3.28 / 3.13
INPUT (kW)	Heating/Cooling (UK)	2.92 / 2.66
STARTING CURRENT (A)		4.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		5.91 / 5.65 [13.7]
FUSE RATING (BS88) - HRC (A)		16
MAINS CABLE No. Cores		5
MAX PIPE LENGTH (m)		50
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg)		3.0


3 Three Phase

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length. High efficiency filter optional.




DIMENSIONS


Front View



Upper View



Back View





Telephone: 01707 282880

 $email: air.conditioning@meuk.mee.com \\ web: www.airconditioning.mitsubishielectric.co.uk$

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881
IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Country of origin: United Kingdom – Japan – Thalland – Malaysia. (Mitsubish) Electric Europe 2015. Mitsubish) electric are trademarks of Mitsubish Electric Europe B.V. The company reserves the right to nake any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public amouncement. Mitsubish Electric is constantly developing and improving its products. All descriptions, listiations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on neguest. Third-party product and branes may be trademarks or registered trademarks of their respective owners.










Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)





Mitsubishi Electric UK's commitment to the environment





