Air Conditioning

Product Information

PCA-RP50KAQ (Single Phase) Standard Inverter Heat Pump Ceiling Suspended System

Making a World of Difference

mr.slim.



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

Key Features

- Stylish indoor unit designed for direct ceiling suspension
- Flush to wall installation for concealment of service connections
- Automatic air speed adjustment
- High/low ceiling height modes



Air Conditioning | Heating Ventilation | Controls



Product Information

PCA-RP50KAQ (Single Phase) **Standard Inverter Heat Pump** Ceiling Suspended System

Making a World of Difference

PCA-RP - INDOOR UNITS		PCA-RP50KAQ
CAPACITY (kW)	Heating (nominal)	5.5 (1.7-6.6)
	Cooling (nominal)	5.0 (2.3-5.6)
	Heating (UK)	4.68 (1.45-5.61)
	Cooling (UK)	4.60 (2.12-5.15)
SHF (nominal & UK)		0.79
COP / EER (nominal)		3.62 / 3.23
SCOP / SEER (BS EN14825)		4.0 / 5.7
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A+ / A+
AIRFLOW (I/s)	Lo-Mi1-Mi2-Hi	167-183-217-250
PIPE SIZE mm (in)	Gas/Liquid	12.7 (1/2") / 6.35 (1/4")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	32-34-37-40
SOUND POWER LEVEL (dBA)		60
DIMENSIONS (mm)	Width x Depth x Height	960 x 680 x 230
WEIGHT (kg)		25
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

Air Conditioning


SUZ-KA - OUTDOOR UNITS		SUZ-KA50VA4
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		52 / 52
SOUND POWER LEVEL (dBA) Cooling		65
WEIGHT (kg)		54
DIMENSIONS (mm)	Width x Depth x Height	840 x 330 x 880
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	1.52 / 1.55
	Heating/Cooling (UK)	1.35/ 1.32
STARTING CURRENT (A)		7.7
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		7.50 / 7.70 [12.4]
FUSE RATING (BS88) - HRC (A)		20
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		30
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg)		1.60

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length. Duty/standby not available on SUZ-KA50/60/71VA4. High efficiency filter optional.




DIMENSIONS


Front View



Upper View



Back View



MITSUBISHI ELECTRIC Changes for the Better

Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

forigin: United Kingdom – Japan – Thaland – Malaysia. «Mitsubishi Electric Europe 2015. Mitsubishi Electric and tradinarians of Mitsubishi Electric Europe B.V. The company reserves th ale any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing wing its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to any's General Conditions of Saka, a coopy of which is available on request. Third-parky product and brand names may be trademarks or registered trademarks of their respective owners.



way.mitsubishielectric.co.uk Mitsubishi Electric UK's commitment to the environment



mitsubishielectric2



Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electriciar/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Misubishi Electrics ai conditioning and heat pump systems contain fluorinated preenhouse gases R410A, R407C and R134a.