# Air Conditioning

## **Product Information**

PEA-RP400GAQ (Three Phase)
Standard Inverter Heat Pump

Large Capacity Ceiling Concealed Ducted System

Making a World of Difference



Our standard large capacity range offers customers all the features and benefits of inverter technology with high static pressure of up to 150Pa whilst being cost effective.

#### **Key Features**

- Static pressure of up to 150Pa
- Long pipe run
- Flexible ducting design



Air Conditioning | Heating Ventilation | Controls



# Air Conditioning

## **Product Information**

### PEA-RP400GAQ (Three Phase) **Standard Inverter Heat Pump**

Large Capacity Ceiling Concealed Ducted System

Making a World of Difference

PEA-RP - INDOOR UNITS		PEA-RP400GAQ 3 Three Phase
CAPACITY (kW)	Heating (nominal)	44.8 (19.0-50.0)
	Cooling (nominal)	38.0 (18.0-44.8)
	Heating (UK)	38.1 (16.15-42.5)
	Cooling (UK)	34.95 (16.55-41.2)
SHF (nominal & UK)		0.75
COP / EER (nominal)		3.14 / 2.72
ENERGY LABEL	Heating/Cooling (nominal)	D/D
AIRFLOW (I/s)	Lo-Hi	2000
PIPE SIZE mm (in)	Gas	28.58 (1 1/8") x2
	Liquid	9.52 (3/8") x2
EXTERNAL STATIC PRESSURE (Pa)		150
SOUND PRESSURE LEVEL (dBA) (50Pa) Lo-Hi		52
DIMENSIONS (mm)	Width x Depth x Height	1947 x 764 x 595
WEIGHT (kg)		130
ELECTRICAL SUPPLY		380-415v, 50Hz
PHASE		Three
POWER INPUT (kW) Nominal / UK		1.55 / 1.38
STARTING CURRENT (A)		8.7
RUNNING CURRENT (A) [MAX]		3.8 [4.6]
FUSE RATING (BS88) - HRC (A)		10
MAINS CABLE No. Cores		5
INTERCONNECTING CABLE No. Cores		3


PUHZ-P - OU	TDOOR UNITS	PUHZ-P200YKAx2 Three Phase	3
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		60 / 58	
WEIGHT (kg)		127	
DIMENSIONS (mm)	Width x Depth x Height	1050 x 330+40 x 1338	
ELECTRICAL SUPPLY		380-415v, 50Hz	
PHASE		Three	
SYSTEM POWER	Heating/Cooling (nominal)	14.27 / 13.97	
INPUT (kW)	Heating/Cooling (UK)	12.70 / 11.88	
STARTING CURRENT (A)		5	
RUNNING CURRENT (A) Heating/Cooling [MAX]		9.88 / 9.47 [19]	
FUSE RATING (BS88) - HRC (A)		20	
MAINS CABLE No. Cores		5	
MAX PIPE LENGTH (m)		100 per outdoor	
MAX HEIGHT DIFFERENCE (m)		30	
CHARGE R410A (kg) - 30m		5.8	

#### 3 Three Phase




#### **DIMENSIONS**


# Front View



#### **Upper View**



#### **Back View**





Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


ke any variation in charical specification to the equipment described, or to thirdness or replace in missuases in unisuases. Electric are trademarks of Missuasis Hectric Lurope B.V. The company reserves the kern any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or pain connucionement. Missuasis Hectric is consistantly developing, virg its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to any Science Conditions of Sala, a copy of which is available on request. Thirtip-pay product and brand markers may be trademarks or registered trademarks of their respective owners.













Mitsubishi Electric UK's commitment to the environment









