Air Conditioning

Product Information

PEAD-RP100JAQ (Single Phase) **Standard Inverter Heat Pump**Ceiling Concealed Ducted System

Making a World of Difference



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

Key Features

- Reduced height entire range only 250mm
- Wider range of external static pressure settings across entire range
- Drain pump included as standard



Air Conditioning | Heating Ventilation | Controls



Product Information

PEAD-RP100JAQ (Single Phase) **Standard Inverter Heat Pump**Ceiling Concealed Ducted System

Making a World of Difference


Air Conditioning


PEAD-RP - INDOOR UNITS		PEAD-RP100JAQ
CAPACITY (kW)	Heating (nominal)	11.2 (4.5-12.5)
	Cooling (nominal)	9.4 (4.9-11.2)
	Heating (UK)	9.5 (3.85-10.65)
	Cooling (UK)	8.65 (4.5-10.3)
SHF (nominal & UK)		0.85
COP / EER (nominal)		3.61 / 3.01
SCOP / SEER (BS EN14825)		3.8 / 4.6
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A/B
AIRFLOW (I/s)	Lo-Mi-Hi	400-483-567
PIPE SIZE mm (in)	Gas	15.88 (5/8")
	Liquid	9.52 (3/8")
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Mi3-Hi	29-34-38
SOUND POWER LEVEL (dBA)		61
DIMENSIONS (mm)	Width x Depth x Height	1400 x 732 x 250
WEIGHT (kg)		41
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4

PUHZ-P - OUTDOOR UNITS		PUHZ-P100VHA4
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		54 / 50
SOUND POWER LEVEL (dBA) Heating/Cooling		70
WEIGHT (kg)		75
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER	Heating/Cooling (nominal)	3.10 / 3.12
INPUT (kW)	Heating/Cooling (UK)	2.76 / 2.58
STARTING CURRENT (A)		12.0
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		16.27 / 15.55 [30.65]
FUSE RATING (BS88) - HRC (A)		32
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		50
MAX HEIGHT DIFFERENCE (m)		30
CHARGE R410A (kg)		3.0

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length.







 Model
 A
 B
 C
 D
 E
 F

 PEAD-RP100JAQ
 1400
 1454
 1500
 1360
 14
 1300



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


Country of origin: United Kingdom — Japan — Thialand — Malaysia. OMitsubishi Bectric Europe 2015. Mitsubishi and Mitsubishi Eelectric are trademarks of Mitsubishi Eelectric Europe 8.V. The company reserves the right to make any variation in technical specification for the equipment described, or to withdraw or replace products without prior notification or public amonoment. Mitsubishi Electric's constraintly developing and improving its products. All descriptors, likistrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on equest. Third-party product and brand armses may be trademarks or present expective owners.













Mitsubishi Electric UK's commitment to the environment





