Air Conditioning

Product Information

PEAD-RP35JAQ (Single Phase)
Standard Inverter Heat Pump
Ceiling Concealed Ducted System

Making a World of Difference



Our Standard Inverter range offers customers all the features and benefits of inverter technology whilst being cost effective.

Key Features

- Reduced height entire range only 250mm
- Wider range of external static pressure settings across entire range
- Drain pump included as standard



Air Conditioning | Heating Ventilation | Controls



Product Information

PEAD-RP35JAQ (Single Phase)
Standard Inverter Heat Pump
Ceiling Concealed Ducted System

Making a World of Difference


Air Conditioning


PEAD-RP - INDOOR UNITS		PEAD-RP35JAQ	
CAPACITY (kW)	Heating (nominal)	4.1 (1.7-5.0)	
	Cooling (nominal)	3.6 (1.4-3.9)	
	Heating (UK)	3.49 (1.45-4.25)	
	Cooling (UK)	3.31 (1.29-3.59)	
SHF (nominal & UK)		0.85	
COP / EER (nominal)		3.69 / 3.42	
SCOP / SEER (BS EN14825)		4.0 / 5.5	
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+ / A	
AIRFLOW (I/s)	Lo-Mi-Hi	167-200-233	
PIPE SIZE mm (in)	Gas	9.52 (3/8")	
	Liquid	6.35 (1/4")	
EXTERNAL STATIC PRESSURE (Pa)		35-50-70-100-150	
SOUND PRESSURE LEVEL (dBA)	Lo-Mi-Mi2-Mi3-Hi	23-27-30	
SOUND POWER LEVEL (dBA)		52	
DIMENSIONS (mm)	Width x Depth x Height	900 x 732 x 250	
WEIGHT (kg)		26	
ELECTRICAL SUPPLY		Fed by Outdoor Unit	
FUSE RATING (BS88) - HRC (A)		6	
INTERCONNECTING CABLE No. Cores		4	

SUZ-KA - OUTDOOR UNITS		SUZ-KA35VA4
SOUND PRESSURE LEVEL (dBA) Heating/Cooling		50 / 49
SOUND POWER LEVEL (dBA) Heating/Cooling		62
WEIGHT (kg)		35
DIMENSIONS (mm)	Width x Depth x Height	800 x 285 x 550
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER	Heating/Cooling (nominal)	1.11 / 1.50
INPUT (kW)	Heating/Cooling (UK)	0.99 / 1.28
STARTING CURRENT (A)		5.1
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		4.90 / 5.10 [9.3]
FUSE RATING (BS88) - HRC (A)		16
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		20
MAX HEIGHT DIFFERENCE (m)		12
CHARGE R410A (kg)		1.15

Notes: All units charged to 7m (35-71), 30m (100-140) pipe length.







 Model
 A
 B
 C
 D
 E
 F

 PEAD-RP35JAQ
 900
 954
 1000
 860
 9
 800



Telephone: 01707 282880

email: air.conditioning@meuk.mee.com web: www.airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)


Courtry of origin: United Kingdom — Japan — Thaland — Malaysia. (Mitsubishi Beotric Europe 2015. Mitsubishi and Mitsubishi Eectric Beotric are trademarks of Mitsubishi Eectric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public amorunoment. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general product and branch and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on enquest. Third-party product and branch armses may be trademark or present engosente contracts.













Mitsubishi Electric UK's commitment to the environment





